

THRONE OIL 15W-40

Description:

It is a superior performance general engine oil which is used all year round for all modern and old petrol-diesel engines operating under different working conditions, has suitable constant stability for the use of the different types of trucks and vans with high engine power required to carry heavy loads in warm weather conditions,

Usage Areas:

It is suitable for use in all types of vehicles, such as passenger cars, vans and minibuses, with petrol and diesel engines.

Benefits and Advantages Provided:

- By means of its high viscosity index, it provides superior protection for all seasons.
- It keeps the engine clean by means of its formulated package additives. It provides saving money with long engine oil change.
- Constant oil pressure reduces oil consumption without falling, without foaming in all kinds of weather and road conditions.
- Reduces maintenance costs and reduces oil consumption the least in older engines.

Performance: It compensates the performance specifications API SL/CF, MAN 271, MB 228.1, MB 229.1.

Typical Properties:

Physical Property	Method	15W-40
Density, g/cm ³ , 15°C	ASTM D 4052	0,887
Kin. Viscosity, cSt, 40°C	ASTM D 445	119,7
Kin. Viscosity, cSt, 100°C	ASTM D 445	15,2
Viscosity Index	ASTM D 2270	132
Pour Point, °C	ASTM D 97	-27
Flash Point, °C	ASTM D 92	230

** The values given in the table are typical and they may vary from production to production.*