

SAE 5W-20 SL-CF

Description:

5W/20 is synthetic based engine oil produced by the excellent combination of the synthetic base oils with the additive packages developed under advanced technology. Thanks to its superior technology, it provides unmatched performance under any climatic and road conditions, in particular during in-city and continuous use.

Usage Areas:

It is suitable for high-speed petrol engines at all operating temperatures for four seasons.

Benefits and Advantages Provided:

- By means of its high viscosity index, it provides superior protection for all seasons.
- It keeps the engine clean by means of its formulated package additives. It provides saving money with long engine oil change.
- Constant oil pressure reduces oil consumption without falling, without foaming in all kinds of weather and road conditions.
- Reduces maintenance costs and reduces oil consumption the least in older engines.

Performance: It compensates the performance specifications API SL/CF; ACEA A5/B5/B4; RN 700.

Tipik Özellikleri:

Fiziksel Özellik	Yöntem	5W-20
Yoğunluk, g/cm ³ , 15°C	ASTM D 4052	0,850
Kin. Viskozite, cSt, 40°C	ASTM D 445	49,32
Kin. Viskozite, cSt, 100°C	ASTM D 445	8,7
Viskozite İndeksi	ASTM D 2270	156
Akma Noktası, °C	ASTM D 97	-33
Parlama Noktası, °C	ASTM D 92	210

* The values given in the table are typical and they may vary from production to production.