

THRONE OIL DOT-4

Description:

It is high quality synthetic brake fluid with high boiling point which is formulated with special additives for use in hydraulic brake systems and meets DOT 4 standard.

Usage Areas:

It is used in hydraulic braking systems and clutches of motor vehicles.

Benefits and Advantages Provided:

- The recycled boiling point temperature in balance is very high ($> 230^{\circ}\text{C}$).
- It provides maximum protection in brake system with its corrosion and oxidation preventive additives and extends service life.
- All kinds of metal parts used in brake systems of modern vehicles are compatible with natural and synthetic felts.
- The freezing point is low.

Performance: It compensates the performance specifications SAE J 1703- J 1704, ISO 4925 ve FMVSS 116 DOT 4.

Typical Properties:

Physical Property	Method	DOT-4
pH	ASTM D 1287	8,1
Density, g/cm^3 , 15°C	ASTM D 4052	1,062
Kin. Viscosity, cSt, 40°C	ASTM D 445	1100
Kin. Viscosity, cSt, 100°C	ASTM D 445	2,2
Boiling Point, $^{\circ}\text{C}$	ASTM D 1120	265
Flash Point, $^{\circ}\text{C}$	ASTM D 93	138

** The values given in the table are typical and they may vary from production to production.*